

## GP3-110 CAMSHAFT TIMING SPECIFICATIONS

**Application:** Triumph 6-cylinder 2498 cc. engine

**Lobe Separation:** 110 degrees

**Recommended Spring Pressure:** 65 - 80 lbs seated, 170 – 180 lbs open

	Duration @ .012 tappet lift	Duration @ .050 tappet lift	Cam lift	Valve lift*	Valve clearance	Center-line
Intake	281	232	.282"	.395"	.017	110 atdc
Exhaust	281	232	.282"	.393"	.019	110 bt dc

\* net valve lift with stock rockers and specified valve clearance.

Check timing at .050 tappet lift

intake open	6 bt dc	intake close	46 ab dc
exhaust open	46 bb dc	exhaust close	6 at dc

Timing at .012 tappet lift (point of valve opening)

intake open	28 bt dc	intake close	73 ab dc
exhaust open	68 bb dc	exhaust close	33 at dc

Time the cam using a degree wheel on the crank and a dial indicator on the push rod. Cam timing may be retarded a few degrees to increase top end torque or advanced a few degrees to increase low end torque. One tooth on the cam chainwheel is 8.5 camshaft degrees (17 crank degrees). Turning the chainwheel ¼ turn on the cam turns the cam ½ tooth or 4.25 cam degrees (8.5 crank degrees). Infinite adjustment may be made by using Good Parts adjustable cam sprocket.

Sample timing points at .050" lift at 4 degrees advanced are as follows:

intake open	10 bt dc	intake close	42 ab dc
exhaust open	50 bb dc	exhaust close	2 bt dc

**Break-in:** Clean the cam well before installing. Lube cam and tappets with cam lubricant when installing. Drive oil pump with electric drill (in reverse) to prime oil system prior to startup. Start engine and run at 2000 – 2500 rpm for 20 minutes without stopping. Stop engine and change oil and oil filter.

**WARNING:** Do not insert the lifters until the camshaft locating plate is bolted in place. Do not bolt the camshaft locating plate onto the block without the main front engine plate in place.



Good Parts Inc.  
Richard Good  
4316 New Holland Rd.  
Mohnton, PA 19540  
(610)777-4457  
goodparts@verizon.net